


100/1000BASE-TX TRANSFORMER MODULES

PartNO:HX82401S



Features:




- Designed for Ethernet 100/1000 BASE-T.
- Supports 8 pairs of category 5 UTP cable.
- Conforms to ANSI/J-STD-002, 245°C reflow peak temperature per IPC/EIA J-STD-003A.
- Compliant with IEEE 802.3at standard for 1000 BASE-T.
- Operating temperature range: -40°C to +85°C.
- Storage temperature range: -55°C to +120°C.

Specifications

Electrical Specification@25° C Operating Temperature -45 to +80° C									
Part NO	Trun Ratio($\pm 2\%$)		OCL primary@100KHz 0.1Vms 8MA	Leakage primary@10KH z 0.1Vms	Cww(Pri:Sec)	DCR(Ω)			
	TX	RX				Primary	Secondary		
HX82401S	1CT:1CT	1CT:1CT	350uH Min	0.5uH max	35PF	0.9Max	1.2Max		
Electrical Specification@25° C Operating Temperature -45 to +80° C									
Part NO	Insertion loss(dB max) 1-100MHz	Return Loss(db min)MHz				CMRR(dB min)MHz		Crosstalk(dB min)MHz	Isolation Voltage(Vrms min)
		1-30	40	50	60-100	1-60	60-100		
HX82401S	-1.2	-18	-14.4	-13.1	-12	-40	-35	-40	1500

Schematic



HQST ELECTRONICSCO.,LTD.

<https://shop104373926.taobao.com/>

石門盈盛电子科技有限公司

TEL:0755-21083343 18673625585

www.wangluobianyaqi.cn

E-mail:hqst008@163.com

Mechanical:

