

Features:




- Designed for Ethernet 100/1000 BASE-T.
- Supports 8 pairs of category 5 UTP cable.
- Cable interface for isolation and low common mode emissions.
- Compliant with IEEE 802.3ab standard for 1000 BASE-T.
- Compliance with ROHS requirements
- Operating temperature range: 0°C to +70°C.
- Storage temperature range: -10°C to +85°C.






Specifications

Electrical Specification@25° C Operating Temperature 0 to +70° C									
Part NO	Trun Ratio(±2%)		OCL primary@100KHz 0.1Vms 8MA	Leakage primary@10KH z 0.1Vms	Cww(Pri:Sec)	DCR(Ω)			
	TX	RX				Primary	Secondary		
H88811D	1CT:1CT	1CT:1CT	350uH Min	0.5uH max	35PF	0.9Max	1.2Max		

Electrical Specification@25° C Operating Temperature 0 to +70° C									
Part NO	Insertion loss(dB max) 1-100MHz	Return Loss(db min)MHz				CMRR(dB min)MHz		Crosstalk(dB min)MHz	Isolation Voltage(Vrms min)
		1-30	40	50	60-100	1-60	60-100		
H88811D	-1.2	-18	-14.4	-13.1	-12	-40	-35	-40	1500

Schematic





Mechanical:

100/1000BASE-TX TRANSFORMER MODULES


PartNO:H88811D



Mechanical:



INNER BOX: 567x135x125



OUTER CARTON: 598x287x150

1. 1 TUBE=17PCS
2. 1 INNER BOX=20TUBE=20x17=340PCS
3. 1 OUTER CARTON=2 INNER BOX=2x340=680PCS

HQSTELECTRONICSCO.,LTD.
<https://shop104373926.taobao.com/>
石门盈盛电子科技有限公司

TEL:0755-21083343 18673625585
www.wangluobianyaqi.cn
E-mail:hqst008@163.com