



HQST-E2259A01A-GY

1.VOLTAGE RATING:	125VAC RMS
2.CURRENT RATING:	1.5 AMP
3.CONTACT RESISTANCE	30 MILLIOHMS MAX
4.INSULATION RESISTANCE	500 MEGOHMS MIN @ 500 VDC
5.DIELECTRIC STRENGTH	1000VAC RMS 50HZ OR 60HZ 1MIN



1.HOUSING & INSERT MATERIAL	GLASS FILLED PA66(UL94V-0)
2.CONTACT MATERIAL	DIAMETER 0.46MM PHOSPHOR BRONZE GOLD PLATING OVER NICKEL
3.SHIELD	0.20~0.25MM THICKNESS BRASS WITH TIN PLATED
4.MATING/UNMATING FORCE	2.2KG.F MAX
5.RETENTION STRENGTH	7.7KG.F MIN BETWEEN JACK AND PLUG
6.OPERATING LIFE	600 CYCLES MIN

1. STORAGE	-40℃~+85℃	RELATIVE HUMIDITY <70%
2. OPERATION	-40℃~+70℃	



HQST ELECTRONICS CO., LTD.

<https://shop104373926.taobao.com/>

湖南省石门县华强盛电子科技有限公司

TEL:18673625585 13302925516

QQ : 278894196 229197143

E-mail:shengzhongting@hotmail.com