


1000 BASE -T MAGNETICS MODULES

P/N: 24SH10410 HF DATA SHEET



Feature



- Designed for long haul gigabit Ethernet 1000 BASE-T, full duplex applications.
- Supports 4 pairs of category 5 UTP cable.
- Cable interface for isolation and low common mode emissions.
- Complying with IEEE 802.3ab standard for 1000 BASE-T.
- Complying with IEEE 802.3af standard.
- Complying with ROHS & Halogen Free requirements.
- Operating temperature range: -10°C to +70°C.
- Storage temperature range: -25°C to +85°C.


Electrical Specifications @ 25°C

Part Number	Turns Ratio (±5%)		OCL (uH Min) @100KHz/0.1V with 8mA DC Bias	Cross talk (dB Min)			HI-POT
	TX	RX		30MHz	60MHz	100MHz	
24SH10410 HF	1CT:1CT	1CT:1CT	350	-45	-40	-35	5000V /1mA /2S

Continue

Part Number	Insertion Loss (dB Max)	Return Loss (dB Min)@Load 100Ω					DCMR (dB Min)		
	1-100MHz	1-30MHz	40MHz	50MHz	60-80MHz	100MHz	30MHz	60MHz	100MHz
24SH10410 HF	-1.0	-18	-14.4	-13.1	-12	-10	-43	-37	-33


Schematic



1000 BASE -T MAGNETICS MODULES
P/N: 24SH10410 HF DATA SHEET



Mechanical



Units: mm[Inches] Tolerances: xx.x0±0.25[0.010]
0.xx±0.05[0.002]