

1 Features




- Meets IEEE 802.3at and ANSI X3.263 standards .RoHS Compliant
- 100/1000Base-T, Surface Mount Type, Open Header
- Cable interface for isolation and low common mode emissions.
- Reflow soldering temperature: peak temperature $\leq 250^{\circ}\text{C}$ (10s)
- Reflow soldering frequency: It is recommended not to exceed 3 times
- Storage temperature range: -40°C to $+85^{\circ}\text{C}$
- Operating temperature range: 0°C to $+70^{\circ}\text{C}$



2 Specifications (特性参数)


Part No	OCL primary@100K Hz 0.1Vrms 8mA	Turns Ratio(3%)	Leakage primary@10K H z 0.1Vrms	DCR (Ω) Max	Cww(Pri:Sec) pF Typ		Isolation Voltage(AC Vrms 1S)
H84807SP	350UH	1:1	0.5uH max	0.9/1.2	35		1500V
Part No	Insertion loss(dB max) 1-100MHz	Return Loss(dB Min)MHz			CMRR(dB min)MHz		Crosstalk (dB min)MHz
		1-30	40~60	60~100	1-60	60~100	1~100
H84807SP	-1.1	-18	-16	-12	-40	-30	-35

3 Mechanical (外观尺寸图)







※unit: mm

4 Schematic (原理图)



5 packing (包装信息)



※unit: mm

※ Packaging quantity : *pcs/roll *pcs/box

※ Outer box size: * L * * W * * H